

Fluoropolymer

NEOFLON FEP NP-130

TECHNICAL
DATASHEET

NEOFLON FEP NP-130 is a melt processable fluoropolymer.

Introduction

- NEOFLON FEP NP-130 is a copolymer of tetrafluoroethylene and hexafluoropropylene.
- Quite similar properties as PTFE. Chemical, electrical and mechanical properties.
- Continuous service temperature is 200°C.
- Improved stress crack resistance with good processability of NP-30.
- Typical applications are thick wall wire and cable insulation, Jacket, tubing, and sheet by extrusion process.

General physical properties

Items	Unit	Numeric Value	Test method
MFR	g/10min	3	ASTM D 2116
Melting Point	°C	255	ASTM D 2116
Specific Gravity	-	2.15	ASTM D 792
Tensile strength	MPa	27	ASTM D 638
Elongation	%	330	ASTM D 638

* The above numeric values are representative and not guaranteed.

Handling method/Safety information

- Be sure to read the notes on SDS and labels before use.
- This product is intended for general industry, and therefore its adequacy and safety as a raw material for medical purposes cannot be guaranteed.

Packing specification

- 25kg

For more information, contact us.

Shenzhen Chuangxin Plastic Technology Co., Ltd.

Tel: +86 18676057437 E-mail: xl1797110736@163.com

<https://www.cxinplas.com>